


JOHNSON & HOFFMAN

a JADE Corporation



Manufacturer of Precision Metal Stampings & Deep Drawn Components



Standard Plugs with Hole Diameters 13/32 to 1-1/8 (10.3-28.6mm)

		Panel Thickness				Cap Dia.		Cap Height		Prong Length			
Hole Dia.		Min		Max								Number Of	J&H Root
In	mm	In	mm	In	mm	In	mm	In	mm	In	mm	Prongs	Part Number
13/32	10.3	.062	1.6	.078	2.0	1/2	12.7	1/16	1.6	3/16	4.8	6	48182
7/16	11.1	.037	0.9	.047	1.2	21/32	16.7	5/64	2.0	5/32	4.0	8	51043
15/32	11.9	.083	2.1	.125	3.2	5/8	15.9	1/16	1.6	19/64	7.5	8	51051
1/2	12.7	.037	0.9	.062	1.6	21/32	16.7	5/64	2.0	3/16	4.8	8	48152
1/2	12.7	.125	3.2	.156	4.0	5/8	15.9	1/16	1.6	21/64	8.3	6	51338
17/32	13.5	.031	0.8	.062	1.6	21/32	16.7	5/64	2.0	3/16	4.8	8	51074
9/16	14.3	.047	1.2	.078	2.0	23/32	18.3	1/16	1.6	7/32	5.6	8	51156
5/8	15.9	.062	1.6	.078	2.0	51/64	20.2	5/64	2.0	13/64	5.2	8	48172
5/8	15.9	.062	1.6	.109	2.8	51/64	20.2	5/64	2.0	7/32	5.6	8	51142
11/16	17.5	.037	0.9	.062	1.6	7/8	22.2	5/64	2.0	3/16	4.8	12	50727
3/4	19.1	.037	0.9	.093	2.4	15/16	23.8	3/32	2.4	13/64	5.2	12	51026
3/4	19.1	.078	2.0	.109	2.8	15/16	23.8	3/32	2.4	17/64	6.8	12	48165
25/32	19.8	.125	3.2	.188	4.8	15/16	23.8	3/32	2.4	19/64	7.5	12	51334
13/16	20.6	.047	1.2	.078	2.0	1 1/16	27.0	1/16	1.6	3/16	4.8	12	51045
7/8	22.2	.031	0.8	.093	2.4	1 1/16	27.0	1/16	1.6	15/64	6.0	12	48155
7/8	22.2	.094	2.4	.171	4.3	1 1/16	27.0	5/64	2.0	19/64	7.5	12	50685
29/32	23.0	.031	0.8	.062	1.6	1	25.4	1/8	3.2	1/4	6.4	12	48189
15/16	23.8	.037	0.9	.094	2.4	1 5/32	29.4	1/16	1.6	7/32	5.6	12	51351
1.0	25.0	.062	1.6	.093	2.4	1 5/32	29.4	5/64	2.0	7/32	5.6	12	48143
1.0	25.4	.093	2.4	.125	3.2	1 5/32	29.4	5/64	2.0	7/32	5.6	12	48166
1 1/16	27.0	.062	1.6	.093	2.4	1 5/16	33.3	3/32	2.4	13/64	5.2	12	51149
1 1/8	28.6	.037	0.9	.078	2.0	1 5/16	33.3	3/32	2.4	1/4	6.4	12	48174

Material Prefix

BS	Brass CDA260
HS	CRS1050
SS	CRS1008/1010
NS	Stainless Steel
XS	CRS1008/1010 - Assembled
XH	CRS1050 - Assembled
XX	CRS1008/1010 & CRS1050 Assembled