



Johnson & Hoffman Plug Buttons



Standard Plugs with Hole Diameters 3/16 to 25/64 (4.8-9.9mm)															
Hole Dia.		Panel Thickness				Cap Dia.		Cap Height				Prong Length		Number Of Prongs	J&H Root Part Number
		Min		Max											
In	mm	In	mm	In	mm	In	mm	In	mm	In	mm				
3/16	4.8	.037	1.0	.062	1.6	11/32	8.7	1/16	1.6	9/64	3.6	6	48179		
7/32	5.6	.037	0.9	.078	2.0	11/32	8.7	5/64	2.0	5/32	4.0	6	50711		
1/4	6.4	.032	6.8	.078	2.0	13/32	10.3	5/64	2.0	11/64	4.4	6	51617		
1/4	6.4	.035	0.9	.062	1.6	13/32	10.3	1/16	1.6	11/64	4.4	6	48151		
9/32	7.1	.032	0.8	.078	2.0	13/32	10.3	1/16	1.6	13/64	5.2	6	51071		
5/16	7.9	.037	0.9	.062	1.6	7/16	11.1	1/16	1.6	3/16	4.8	6	51034		
11/32	8.7	.093	2.4	.125	3.2	17/32	13.5	5/64	2.0	19/64	7.5	6	48149		
3/8	9.5	.015	0.4	.039	1.0	35/64	13.9	5/64	2.0	9/64	3.6	6	51077		
3/8	9.5	.037	0.9	.078	2.0	1/2	12.7	1/16	1.6	11/64	4.4	6	48192		
3/8	9.5	.093	2.4	.171	4.3	17/32	13.5	5/64	2.0	19/64	7.5	6	48154		
25/64	9.9	.078	2.0	.093	2.4	1/2	12.7	1/16	1.6	3/16	4.8	6	51003		

Material Prefix	
BS	Brass CDA260
HS	CRS1050
SS	CRS1008/1010
NS	Stainless Steel
XS	CRS1008/1010 - Assembled
XH	CRS1050 - Assembled
XX	CRS1008/1010 & CRS1050 Assembled